

CHASSIS SPECS

2016 Cornerstone (45' K3)

Premium Chassis Features

- Cummins 2013 ISX 600 hp Electronic Diesel Engine
- Hadley SLS Automatic Air Leveling
- 3 Stage Engine Compression Brake
- VIP Smart Wheel with Integrated Radio Controls
- Suspended Adjustable Pedals
- Independent Front Suspension
- Allison GEN 5 Transmission & Touch Pad

- Polished Aluminum Wheels w/Dress Kit
- Air Disc Brakes on All (3) Axles
- Automatic Traction Control
- 20,000 lb Hitch
- 3 Year / 50,000 Mile Warranty:
 - No Deductible, 24/7 Roadside Assistance
- Lifetime Warranty on Frame & Cross Members

Chassis Weight Rating	GVWR	Front GAWR	Rear GAWR	Tag GAWR	GCWR
	54,000 lb	20,000 lb	20,000 lb	14,000 lb	74,000 lb
Engine		Peak Horsepov	wer	Peak Torque	
Cummins 2013 ISX15 • 18.7 CFM Air Compressor • 1,500 Watt Block Heater	600 hp @ 1,800 rpm			1,950 lb-ft @	1,200 rpm
Transmission	Ratios: 1st	2nd	3rd 4th	5th 6	th Rev

Transmission	Ratios:	1st	2nd	3rd	4th	5th	6th	Rev
Allison GEN 5 - 4000MH Electronic, 6-Speed with (2) Overdrives Push-Button Shift Pad Allison Fuel Sense Plus		3.51	1.91	1.43	1.00	0.74	0.64	-4.80

Front Axle	Capacity	Track Width
Reyco Granning IFS2000	20,000 lb	86.5"

Rear Axle	Capacity	Track	Ratio	Tag Axle Capacity	Tag Track
Meritor RC-23-161	23,000 lb	73.1"	4.30:1 "Quiet-Gear"	14,000 lb	85.8"

Suspension	Shock Absorber
Front: Reyco Granning IFS2000	Bilstein Shocks Front: 60mm
Rear: Ridewell 246	Rear: 46mm
Tag: Ridewell 246	Tag: 46mm

Brakes	Parking	Auxiliary	ABS
Air Disc Brakes	Push/Pull Knob	Three-Stage Engine Compression Brake	WABCO 6S/6M ABS System



2016 Cornerstone (45' K3)

Steering	Column	Gear	Turn Angle
VIP Soft Touch, Wood Grain & Leather-Wrapped Smart Wheel w/Integrated Radio Controls	Douglas Autotech Tilt & Telescoping Column		55°

Cooling System

Side-Mounted Radiator: 1,891 sq.in. Parallel Air Flow System with Low Profile Radiator, Charge Air Cooler Utilizing a Modulated Engine-Driven Cooling Fan

Electrical System	Alternator	Batteries
Custom Modular Electrical System	210 amp Leece-Neville Alternator	(2) Harris 950 CCA Batteries

Fuel System

- 150 gal Fuel Tank with Dual Side Fill
- Side-Mounted Fuel Level Sender
- 15 gal DEF Tank

Frame	Top Rail	Bottom Rail
Rear-Engine Raised Rail Design for Increased Storage	8.25" x 3.5" x 0.38"	Front: 10.25" x 3.5" x 0.38" Rear: 10.25" x 3.5" x 0.38" Lower: 10.00" x 3.0" x 0.25" Box
Wheel Base	Front Overhang	Rear Overhang
320"	71.00"	128.25"

Wheels

- (6) Alcoa Polished Aluminum Wheels with Dress Kit
- (2) Steel Wheels on Inside Dual Wheels

Tires

Front: Michelin 365/70R22.5 XZA LRL **Rear:** Michelin 315/80R22.5 XZA1 LRL **Tag:** Michelin 315/80R22.5 XZA1 LRL

The information in this literature reflects product specifications at the date of printing. Spartan Chassis and its OEMs reserve the right, at any time, to make changes in product design, material or component specifications as its sole option, without notice. All information printed in this literature is subject to change.

Printed 3/2015

