



FOR

ENTEGR
COACH®

CHASSIS SPECIFICATIONS

2017 ENTEGRA ANTHEM

42' & 44' 

PREMIUM CHASSIS FEATURES

- VIP Smart Wheel with Integrated Radio Controls
- Suspended Adjustable Pedals
- 2 Stage Engine Compression Brake
- Independent Front Suspension
- 12,000 lb. Tag Axle
- Allison Transmission and Touch Pad
- Automatic Traction Control (ATC)
- Automatic Heated Moisture Ejectors w/Color Coded Lanyards
- 15,000 lb Towing Capacity
- 3 Year / 50,000 Mile Warranty: No Deductible, 24/7 Roadside Assistance
- 20 Year Transferrable Warranty on Frame & Cross Members

Chassis Weight Rating	GVWR	Front GAWR	Rear GAWR	Tag GAWR	GCWR
	49,000 lb	17,000 lb	20,000 lb	12,000 lb	64,000 lb

Engine	Peak Horsepower	Peak Torque
Cummins ISL9 • 18.7 CFM Air Compressor • 1,000 Watt Block Heater	450 hp @ 2,100 rpm	1,250 lb-ft @ 1,400 rpm

Transmission	Ratios: 1st	2nd	3rd	4th	5th	6th	Rev
Allison - 3000MH 6-Speed with Push-Button Shift Pad Allison Fuel Sense	3.49	1.86	1.41	1.00	0.75	0.65	-5.03

Front Axle	Capacity	Track Width
Reyco Granning IFS1700	17,000 lb	85.8"

Rear Axle	Capacity	Track	Ratio	Tag Axle Capacity	Tag Track
Meritor RS-19-144	20,000 lb	72.1"	4.88:1	12,000 lb	85.7"

Suspension	Shock Absorber
Front: Reyco Granning IFS1700 Rear: Hendrickson HTB210 Tag: Hendrickson TBT	Bilstein Shocks Front: 60mm Rear: 46mm Tag: 46mm

Brakes	Parking	Auxiliary	ABS
Front: Air Disc Brakes Rear: 16.5" x 7.0" Air Drum Brakes Tag: 16.5" x 5.0" Air Drum Brakes	Push/Pull Knob	Two-Stage Engine Compression Brake	WABCO 6S/6M ABS System



FOR

ENTEGR
COACH®

2017 ENTEGRA ANTHEM

42' & 44'



Steering	Column	Gear	Turn Angle
VIP Soft Touch, Wood Grain & Leather Smart Wheel w/Integrated Radio Controls	Douglas Autotech Tilt and Telescoping Column	ZF-8098	55°
Cooling System			
Side-Mounted Radiator: Parallel Air Flow System with Low Profile Radiator, Charge Air Cooler and Remote Mounted Hydraulic Oil Cooler with a Modulated Hydraulic-Driven Cooling Fan			
Electrical System	Alternator	Batteries	
Custom Modular 12v Electrical System	170 amp Leece-Neville Alternator	(2) Harris 950 CCA Batteries	
Frame	Top Rail	Bottom Rail	
Rear Engine Raised Rail Design for Increased Storage	8.25" x 3.5" x .38"	Front: 9.00" x 2.75" x .38" Rear: 8.25" x 3.5" x .38"	
Fuel System	Exhaust System		
<ul style="list-style-type: none"> • 150 gal Fuel Tank with Dual Side Fill 	<ul style="list-style-type: none"> • 15 gal DEF Tank with Dual Side Fill • Chrome Tailpipe, 4" OD 		
Wheel Base	Front Overhang	Rear Overhang	
42'—296" 44'—320"	71"	123"	
Wheels			
(6) Accuride Polished Aluminum Wheels with Dress Kit (2) Steel Wheels on Inside Dual Wheels			
Tires			
Front: Michelin XZA1 315/8R22.5 LRL Rear: Michelin XZA2 295/80R22.5 LRH Tag: Michelin XZA2 295/80R22.5 LRH			

The information in this literature reflects product specifications at the date of printing. Spartan Motors and its OEMs reserve the right, at any time, to make changes in product design, material or component specifications as its sole option, without notice. All information printed in this literature is subject to change.

